


M8 female connector 90° with cable PUR-OB 4x0,25 grey drag chain 10m

Female 90°  
4-pole

## Image



## Approvals



## Form

08101

## Technical Data

Operating voltage	30 V AC/DC
Supply current per contact (40 °C)	max. 4 A
Fixing	Screw thread M8 x 1 mm <sup>2</sup> (recommended torque = 0.4 Nm) self-securing
Protection	IP67
Temperature range	-25...+85 °C, depending on cable quality

## Cable


No. and diameter of wires	4 x 0.25 mm <sup>2</sup>
Wire isolation	PP (br, wh, bl, bk)
Suitable for C-tracks	yes
Jacket	PUR (UL/CSA)
Outer diameter	approx. 4.4 mm
Bend radius (mobile)	10 x outer diameter
Temperature range (fixed)	-50...+80 °C
Temperature range (mobile)	-25...+80 °C

## Commercial data

Gross weight	293
Net weight	293
Weight unit	gram
Basic unit	pc.
Customs tariff number	85444290
Unit (piece)	1
Limited value	1

## Comments

Plastic housings with good resistance against chemicals and oils.  
The resistance to aggressive media should be individually tested for your application. Further details on request.  
Further cable lengths on request.

**Circuit diagram****Contact layout**

## Female

