

**M12-Steel female connector straight with cable TPE-OB 4x0,34 grey UL, CSA + drag chain 5m**

Female straight  
4-pole

**Image****Approvals****Form**

12221

**Technical Data**

|                                    |                                                                                  |
|------------------------------------|----------------------------------------------------------------------------------|
| Operating voltage                  | 32 V AC/DC                                                                       |
| Supply current per contact (40 °C) | max. 4 A                                                                         |
| Fixing                             | screw thread M12 x 1 mm <sup>2</sup> (recommended torque = 0.6 Nm) self-securing |
| Protection                         | IP68/69K                                                                         |
| Temperature range                  | -40...+85 °C                                                                     |

**Cable**


|                            |                          |
|----------------------------|--------------------------|
| No. and diameter of wires  | 4 x 0.34 mm <sup>2</sup> |
| Wire isolation             | TPE-S (br, wh, bl, bk)   |
| Suitable for C-tracks      | yes                      |
| Jacket                     | TPE-S                    |
| Outer diameter             | approx. 5.2 mm           |
| Bend radius (mobile)       | 15 x outer diameter      |
| Temperature range (fixed)  | -50...+125 °C            |
| Temperature range (mobile) | -30...+105 °C            |

**Commercial data**

|                       |          |
|-----------------------|----------|
| Gross weight          | 208      |
| Net weight            | 208      |
| Weight unit           | gram     |
| Basic unit            | pc.      |
| Customs tariff number | 85444290 |
| Unit (piece)          | 1        |
| Limited value         | 1        |

**Comments**

Further cable lengths on request.

**Circuit diagram****Contact layout****Female**