

M12 male straight / M12 female straight PVC-OB 4x0,34 grey 2m

Male straight to female straight

M12 - M12

4-pole

Image**Approvals****Form**

40021

Technical Data

Operating voltage	max. 250 V AC/DC
Current per contact (40 °C)	max. 4 A
Fixing	screw thread M12 x 1 mm ² (recommended torque = 0.6 Nm) self-securing
Protection	IP67
Temperature range	-25...+85 °C, depending on cable quality

Cable


No. and diameter of wires	4 x 0.34 mm ²
Wire isolation	PVC (br, wh, bl, bk)
Suitable for use in C-tracks	no
Jacket	PVC
Outer diameter	approx. 5.0 mm
Bend radius (mobile)	10 x outer diameter
Temperature range (fixed)	-30...+70 °C
Temperature range (mobile)	-5...+70 °C

Commercial data

Gross weight	100,000
Net weight	100,000
Weight unit	Gramm
Basic unit	ST
Customs tariff number	85444290
Unit (piece)	1,000
Limited value	1,000

Comments

Picture shows variant with yellow jacket
 Plastic housings with good resistance against chemicals and oils.
 The resistance to aggressive media should be individually tested for your application. Further details on request.
 Further cable lengths on request.

Circuit diagram**Contact layout**