

M12 male straight / M12 female straight PVC-JB 5x0,34 grey 2m

Male straight to female straight

M12 - M12

5-pole

Image**Approvals****Form**

40041

Technical Data

Operating voltage	max. 125 V AC/DC
Supply current per contact (40 °C)	max. 4 A
Fixing	screw thread M12 x 1 mm ² (recommended torque = 0.6 Nm) self-securing
Protection	IP67
Temperature range	-25...+85 °C, depending on cable quality

Cable

No. and diameter of wires	5 x 0.34 mm ²
Wire isolation	PVC (br, wh, bl, bk, gnye)
Suitable for C-tracks	no
Jacket	PVC
Outer diameter	approx. 5.2 mm
Bend radius (mobile)	10 x outer diameter
Temperature range (fixed)	-30...+70 °C
Temperature range (mobile)	-5...+70 °C


Commercial data

Gross weight	135
Net weight	135
Weight unit	gram
Basic unit	pc.
Customs tariff number	85444290
Unit (piece)	1
Limited value	1

Comments

Plastic housings with good resistance against chemicals and oils.
 The resistance to aggressive media should be individually tested for your application. Further details on request.
 Further cable lengths on request.

Circuit diagram



at cable types with (*) wire color gray

Contact layout

