

Exact8, 4xM8, 3-pole, moulded cable 10.0m PUR 4x0,34+2x0,75 exit norm..

4-way, 3-pole

PUR (UL/CSA), halogen free

10.0 m

Image



Approvals



Contact layout

Contact 1	(+)	
Contact 3	(-)	
Contact 4	(N/O)/(S1)	
LED display	LED (green): Power	LED (yellow): signal (S1)

All data on this data sheet was compiled carefully.

Liability regarding correctness, completeness, and actuality is limited to gross negligence. Created: 03/11

Murrelektronik GmbH | Falkenstraße 3, D-71570 Oppenweiler | Fon +49 7191 470, Fax +49 7191 47-130 | info@murrelektronik.com | www.murrelektronik.com

Technical Data

Operating voltage	24 V DC
Signal per port	1
Operating current per contact (40 °C)	max. 2 A
Housing	Plastic, flame retardant
Protection	IP67
Temperature range	-20...+80 °C, depending on cable quality
Total current	max. 8 A

Technical data M8 port

Locking of ports	Screw thread M8 x 1 mm
------------------	------------------------

Cable

No./diameter of wires	4 × 0.34 + 2 × 0.75 mm ²
Jacket	PUR (UL/CSA), halogen free
Outer diameter	approx. 7.6 mm
Bend radius (mobile)	10 x outer diameter
Temperature range (fixed)	-40...+80 °C
Temperature range (mobile)	-5...+80 °C
Bend cycles	5 Mio.

General data

Protection	IP65, IP67
------------	------------


Commercial data

Gross weight	887
Net weight	887
Weight unit	gram
Basic unit	pc.
Customs tariff number	85444290
Unit (piece)	1
Limited value	1

Comments

Further cable lengths on request.
 Plastic housings with good resistance against chemicals and oils.
 The resistance to aggressive media should be individually tested for your application. Further details on request.

Contact layout



Circuit diagram

