

Exact8, 4xM8, 4-pole, moulded cable 5.0m PUR 8x0,34+2x0,75, UL/CSA

4-way, 4-pole
PUR, halogen free
5.0 m

Image



Approvals



Contact layout

Contact 1	(+)
Contact 2	(N/C)/(S2)
Contact 3	(-)
Contact 4	(N/O)/(S1)
LED display	LED (green): Power LED (yellow): signal (1) LED (white): Signal (2)

Technical Data

Operating voltage	24 V DC
Supply voltage indicator	LED (green)
Signal per port	2
Supply current per contact (40 °C)	max. 2 A
Total current	max. 10 A
Comments	The applicable current loads and overload limits of the cables, as defined by the specific standard, must be taken into consideration

Technical data M8 port

Locking of ports	Screw thread M8 x 1 mm ²
------------------	-------------------------------------

Cable

No. and diameter of wires	8 x 0.34 + 2 x 0.75 mm ²
Jacket	PUR, halogen free
Outer diameter	approx. 9.2 mm
Bend radius (mobile)	10 x outer diameter
Bend cycles	5 mio.

General data

Housing	Plastic, flame retardant
Protection	IP67
Temperature range	-20...+80 °C, depending on cable quality

Commercial data

Gross weight	645
Net weight	645
Weight unit	gram
Basic unit	pc.
Customs tariff number	85444290
Unit (piece)	1
Limited value	1

All data on this data sheet was compiled carefully.

Liability regarding correctness, completeness, and actuality is limited to gross negligence. Created: 06/10

Comments

Further cable lengths on request.

Plastic housings with good resistance against chemicals and oils.

The resistance to aggressive media should be individually tested for your application. Further details on request.

Contact layout

M8 Females
4-pole

