

**Exact8, 8xM8, 4-pole, moulded cable 5.0m PUR 16x0,34+2x0,75, UL/CSA**

8-way, 4-pole  
PUR (UL/CSA), halogen free  
5.0 m

**Image**



**Approvals**




**Contact layout**

Contact 1	(+)
Contact 2	(N/C)/(S2)
Contact 3	(-)
Contact 4	(N/O)/(S1)
LED display	LED (green): Power    LED (yellow): signal (S1)    LED (white): Signal (S2)

<b>Technical Data</b>	
Operating voltage	24 V DC
Operating voltage indicator	LED (green)
Signal per port	2
Operating current per contact (40 °C)	max. 2 A
Protection	IP67
Housing	Plastic, flame retardant
Temperature range	-20...+80 °C, depending on cable quality
Total current	max. 8 A
<b>Technical data M8 port</b>	
Locking of ports	Screw thread M8 x 1 mm
<b>Cable</b>	
No./diameter of wires	16 × 0.34 + 2 × 0.75 mm <sup>2</sup>
Jacket	PUR (UL/CSA), halogen free
Outer diameter	approx. 10.4 mm
Bend radius (mobile)	10 x outer diameter
Temperature range (fixed)	-40...+80 °C
Temperature range (mobile)	-5...+80 °C
Bend cycles	5 Mio.
<b>General data</b>	
Protection	IP65, IP67
<b>Commercial data</b>	
Gross weight	886
Net weight	886
Weight unit	gram
Basic unit	pc.
Customs tariff number	85444290
Unit (piece)	1
Limited value	1
<b>Comments</b>	
Further cable lengths on request.	
Plastic housings with good resistance against chemicals and oils.	
The resistance to aggressive media should be individually tested for your application. Further details on request.	

## Contact layout



## Circuit diagram

