

Q40	
●	
15 mm	
PBT RESIN	
●	
Top view dimensions: 46mm, 60mm, 40mm, 30mm. Side view dimensions: 40mm, 118mm, 11mm.	
20-250VAC	
-	
<2.5mA	
400mA	
2.5mA	
5A(20ms)	
5mA	
<8VAC AT 400MA	
<25HZ	
10ms/10ms	
<15%(Sr)	
<1.0%(Sr)	
IP67	
-25 °C - +70 °C	
<10%(Sr)	
-	
-	
-	
RFI>3V/m / EFT>1KV / ESD>4KV (contact)	
IEC 60947-5-2,Part 7.4.1 / IEC 60947-5-2,Part 7.4.2	
PBT	
FQP1-4015A-A2L	9
FQP1-4015A-B2L	10
FQP1-4015A-C4L	13
Approx.250 g	

Q40	
●	
20 mm	
PBT RESIN	
●	
Top view dimensions: 46mm, 60mm, 40mm, 30mm. Side view dimensions: 40mm, 118mm, 11mm.	
20-250VAC	
-	
<2.5mA	
400mA	
2.5mA	
5A(20ms)	
5mA	
<8VAC AT 400MA	
<25HZ	
10ms/10ms	
<15%(Sr)	
<1.0%(Sr)	
IP67	
-25 °C - +70 °C	
<10%(Sr)	
-	
-	
-	
RFI>3V/m / EFT>1KV / ESD>4KV (contact)	
IEC 60947-5-2,Part 7.4.1 / IEC 60947-5-2,Part 7.4.2	
PBT	
FQP2-4020A-A2L	9
FQP2-4020A-B2L	10
FQP2-4020A-C4L	13
Approx.250 g	

Q40	
○	
30 mm	
PBT RESIN	
●	
Top view dimensions: 46mm, 60mm, 40mm, 30mm. Side view dimensions: 40mm, 118mm, 11mm. PG13.5 or 1/2"-14NPT.	
20-250VAC	
-	
<2.5mA	
400mA	
2.5mA	
5A(20ms)	
5mA	
<8VAC AT 400MA	
<25HZ	
10ms/10ms	
<15%(Sr)	
<1.0%(Sr)	
IP67	
-25 °C - +70 °C	
<10%(Sr)	
-	
-	
-	
RFI>3V/m / EFT>1KV / ESD>4KV (contact)	
IEC 60947-5-2,Part 7.4.1 / IEC 60947-5-2,Part 7.4.2	
PBT	
FQP2-4030A-A2L	9
FQP2-4030A-B2L	10
FQP2-4030A-C4L	13
Approx.250 g	