


# KVT-ER

## Split Cord Grips



Certified protection class  
IP65/IP66/IP67/IP68



Slit KT grommets

### Product Description

KVT-ER are split cord grips for routing and sealing cables with and without connectors, conduits or pneumatic hoses with diameters from 1 to 16 mm (KT 1 - 15) and 16 to 35 mm (KT 16 - 34).

Due to the injected gasket and if single-hole grommets are used, the KVT-ER provides certified protection ratings IP65/IP66/IP67/IP68.

The KVT-ER sizes are based on metric standard cut-outs M25, M32, M50 and M63. Hexagonal locknuts are included in the shipment.

For assembly, we recommend to tighten the cover lid screws with max. 2 N m.

### Locknuts

Locknuts with special cut-outs are available separately.



**KGM-SUB-D9** fits D-Sub 9 connectors  
(Required wall cut-out:  $\varnothing$  36 mm / 1.417", PU: 10)  
■ Order No. 45106

**KGM-SUB-D25** fits SUB-D25 connectors  
(Required wall cut-out:  $\varnothing$  50 - 54 mm / 1.969 - 2.126", PU:10)  
■ Order No. 45110

| Description | Type        | Order No. | Grommets KT<br>small   large | Thread<br>Thread length                  | PU |
|-------------|-------------|-----------|------------------------------|--|----|
|             | KVT-ER 25*  | 45450     | 1 -                          | M25 x 1.5<br>Length: 18 mm /<br>0.709"   | 10 |
|             | KVT-ER 32   | 45452     | 1 -                          | M32 x 1.5<br>Length: 18 mm /<br>0.709"   | 10 |
|             | KVT-ER 50 2 | 45454     | 2 -                          | M50 x 1.5<br>Length: 20.5 mm /<br>0.709" | 5  |

\* Max. cable diameter of 15 mm / 0.591"

# KVT-ER Split Cord Grips



Injected elastomer gasket



Slit KT grommets



1.12

| Description | Type        | Order No. | Grommets KT<br>small   large | Thread<br>Thread length                      | PU |
|-------------|-------------|-----------|------------------------------|--|----|
|             | KVT-ER 63 1 | 45455     | - 1                          | M63 x 1.5<br>Length:<br>20.5 mm /<br>0.807 " | 5  |
|             | KVT-ER 63 4 | 45456     | 4 -                          | M63 x 1.5<br>Length:<br>20.5 mm /<br>0.807 " | 5  |

## Advantages & benefits

- Certified protection class IP65/IP66/IP67/IP68 according to EN 60529
- Very high strain relief according to EN 62444
- Warranty of pre-terminated cables remains
- Retrofits, repairs and maintenance can be done easily and quickly
- High cable density
- Suitable for metric cut-outs
- Hexagonal nut included in the delivery
- Anti-corrosive V2A stainless steel screws
- Very robust housing, vibration resistant
- Modern design

## Specifications

|                       |   |
|-----------------------|---|
| Material              | Frame: Polypropylene (PP)<br>Injected gasket: Elastomer                                       |
| Flame class           | UL94-Vo, self-extinguishing   |
| IP rating             | IP65/IP66/IP67/IP68, if correctly assembled with single grommets (certified acc. to EN 60529) |
| Operating temperature | - 40°C to + 110°C (static)<br>- 40° F to + 230° F (static)                                    |
| Properties            | Halogen-free, silicone-free   |
| Cut-out dimension     | Metric sizes  |

## Accessories

|                   |           |
|-------------------|-----------|
| KT Cable grommets | 48 - 50   |
| KVT-EMC Brackets  | 141       |
| Locknuts          | 188 - 189 |
| ST Plugs          | 53        |