

KEL 10

Cable entry frames



1

Product description

The KEL-10 matches exactly the cut-out dimensions of 10-pole standard industrial connectors.

The split insert matching the cable diameter is placed around the cable and inserted into the cable entry frame.

Either a cut out of 36mm or 46mm tall can be chosen depending on the cables being routed. This flexibility is perfect for pre-terminated cables.

Advantages

- Warranty of pre-terminated cables remains
- Retrofitting and maintenance can be carried out easily and quickly
- High packing density, wide variety of frames and inserts
- Strain relief according DIN EN 50262

Specificationen

| | |
|--------------------|---|
| Material | Polyamide |
| Flame class | UL-94 Vo, self-extinguishing |
| Protection class | IP 54, with gasket and correct selection of the cable inserts |
| Temperature | - 40°C to + 140°C (static) |
| Properties | halogen-free, silicone-free |
| Cut-out dimensions | 36 x 65 mm / page 94 |

Accessories

| | |
|-------------------------|--------------|
| KT Cable inserts | Page 22 26 |
| KEL-SNAP SNAP frames | Page 15 |
| KEL-EMC Cable collector | Page 74 75 |

| Description | Type | Order No. | Inserts KT small large | PU |
|-------------|---------------|-----------|-----------------------------|----|
| | KEL 10 6 | 42216 | 6 - | 10 |
| | KEL 10 3 | 42212 | 2 1 | 10 |