


KT Inserts, small



Type	Order No grey	Order No black	Clamping range	PU	Description
KT 2 2	39935	39936	2x Ø 2 mm	10	KT 2 x
KT 2 3	39939	39940	2x Ø 3 mm	10	
KT 2 4	39906	39907	2x Ø 4 mm	10	KT 4 x
KT 2 5	41200	39904	2x Ø 5 mm	10	
KT 2 6	41201	39905	2x Ø 6 mm	10	KT ASI2 rl
KT 2 7	41202	39916	2x Ø 7 mm	10	
KT 2 8	39917	39918	2x Ø 8 mm	10	KT ASI2 ll
KT 4 2	39937	39938	4x Ø 2 mm	10	
KT 4 3	39914	39915	4x Ø 3 mm	10	KTRS
KT 4 4	39909	39911	4x Ø 4 mm	10	
KT 4 5	39908	39910	4x Ø 5 mm	10	KT tele
KT 4 6	39932	39933	4x Ø 6 mm	10	
KT-ASI	39902	39903	1 ASI-cable	10	KT oval
KT-ASI2 rl	39922	39924	2 ASI-cables	10	
KT-ASI2 ll	39921	39923	2 ASI-cables	10	KT S1
KTRS 12	39990	-		10	
KTRS 13	39992	-		10	
KTRS 16	39996	-		10	
KT tele	39929	-	Telephone cable	10	
KT oval	39930	-		10	
KT S1	39931	-		10	

Product description

KT cable inserts small are used with the following cable entry frames:

- KEL - Page 6 - 13
- KEL-FG - Page 14
- KVT - Page 16 - 17
- KVT-W90 - Page 18

The model range KT small is designed for cable diameters from 2 to 17mm.

Assembly

When installing the insert, the smooth side of the insert faces the middle of the cable entry frame.

Specification KT grey

Material	Elastomer
Flame class	UL-94 Vo, self-extinguishing
Temperature	- 30°C to + 90°C (static)
Properties	halogen-free, silicone-free

Specification KT black

Material	Elastomer
Flame class	UL-94 HB
Temperature	- 30°C to + 90°C (static)
Properties	higher chemical resistance, UV-stabilized