







MIN Series Size III Cordsets

North American Color Code ❖ Polyurethane Cable ❖ 18, 22 AWG 300V Plugs

MIN Series Size III Cordsets

Face View of Male	# of Poles	Color Code		Wire AWG Rating	Length	Female Plugs	Male Plugs
	9	1-Orange 2-Blue 3-Red w/ Black 4-Green w/ Black 5-White	6-Red 7-Green/Yellow 8-White w/ Black 9-Black	18 300V 4A	3 FT 6 FT 12 FT 20 FT 30 FT	MINP-9FPX-3 MINP-9FPX-6 MINP-9FPX-12 MINP-9FPX-20 MINP-9FPX-30	MINP-9MPX-3 MINP-9MPX-6 MINP-9MPX-12 MINP-9MPX-20 MINP-9MPX-30
	10	1-Orange 2-Blue 3-White w/ Black 4-Red w/ Black 5-Green w/ Black	6-Orange w/ Black 7-Red 8-Green/Yellow 9-Black 10-White	18 300V 4A	3 FT 6 FT 12 FT 20 FT 30 FT	MINP-10FPX-3 MINP-10FPX-6 MINP-10FPX-12 MINP-10FPX-20 MINP-10FPX-30	MINP-10MPX-3 MINP-10MPX-6 MINP-10MPX-12 MINP-10MPX-20 MINP-10MPX-30
	12	1-Orange 2-Blue 3-White w/ Black 4-Red w/ Black 5-Green w/ Black 6-Orange w/ Black	7-Blue w/ Black 8-Black w/ White 9-Green/Yellow 10-Red 11-White 12-Black	18 300V 4A	3 FT 6 FT 12 FT 20 FT 30 FT	MINP-12FPX-3 MINP-12FPX-6 MINP-12FPX-12 MINP-12FPX-20 MINP-12FPX-30	MINP-12MPX-3 MINP-12MPX-6 MINP-12MPX-12 MINP-12MPX-20 MINP-12MPX-30
	19	1-Violet 2-Red 3-Gray 4-Red w/ Blue 5-Blue 6-Green 7-Brown 8-White w/ Green 9-White w/ Yellow 10-White w/ Gray	11-Black 12-Green/Yellow 13-Yellow w/ Brown 14-Brown w/ Green 15-White 16-Yellow 17-Pink 18-Gray w/ Brown 19-Gray w/ Pink	18/3 300V 8A ----- 22/16 300V 3A	 2 M* 4 M* 6 M* 10 M*	MINP-19FP-2M MINP-19FP-4M MINP-19FP-6M MINP-19FP-10M	MINP-19MP-2M MINP-19MP-4M MINP-19MP-6M MINP-19MP-10M

* 19 Pole Plugs have a foil shield and are measured in meters. Pins 5, 7, and 12 have 18 AWG wires.

For Stainless Steel coupling nut, add a "-SS" suffix (e.g. MINP-9FPX-6 becomes MINP-9FPX-6-SS).

Specifications:

Body: Oil Resistant Yellow PUR
Contacts: Copper Alloy with Gold Plating
Coupling Nut: Clear Anodized Aluminum
Cable: Oil Resistant Yellow PUR Jacket,
 Rated at 300V, 80°C, Non-Wicking,
 Non-Hygroscopic, AWM Style 20233
 19 Pole Plug has a foil shield and black jacket
Conductors: 18 AWG Bare Copper, PVC Insulated
 22 AWG Bare Copper, PVC Insulated
Temperature: -40°C to +80°C (-40°F to +176°F)
Protection: IP 67
Approvals: U.S.: UL Recognized
 Canada: C-UL Recognized
 19 Pole: U.S.: UL Pending
 Canada: C-UL Pending

