





SPECIFICATIONS

REV.

Α

TABLE A	
P/N	L
MIN-19MR-1	12"
MIN-19MR-2	24"
MIN-19MR-3	36"
MIN-19MR-6	72"
MIN-19MR-10	120'

DATE

2/23/2005

APPROVED

FOR LENGTHS OF 24" AND LONGER, A LOCKNUT IS SUPPLIED WITH RECEPTACLE

2

DESCRIPTION

REDRAWN IN SW

REVISIONS

	MATERIALS:	
١		
	SHELL:	CLEAR ANODIZED ALUMINUM
	INSERT:	YELLOW PVC
	CONTACTS:	GOLD PLATED COPPER ALLOY
	WIRE:	18 & 22AWG UL1007
	O-RING:	NBR

' "	1100 0 0 7		
AL	L OTHERS		
PROPRIETARY AND CONFIDENTIAL	VOLTS		
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY			
REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS	TEMP		
PROHIBITED.	SPEC		

\neg		UNLESS OTHERWISE SPECIFIED:		NAME	MENCOM CORPORA		NA COPPOP	A COPPODATION		
\dashv	GROUND	DIMENSIONS ARE IN INCHES	DRAWN	BEM			AIIC	ПОП		
-			CHECKED		TITLE:					
_	300V, 10A		ENG APPR.							
300V, 3A			MFG APPR.			CP				
	0001		Q.A.			. ,	. 02//// (22/(2)			
	300V	MATERIAL	COMMENTS:		SIZE DWG. NO.			RE		
	105°C	FINISH			В	٨	MIN-19MR-ZZ		F	
ECIF	ICATIONS	DO NOT SCALE DRAWING			SCALE: 3:2 WEIGHT: SHI		SHEE	T 1 OI		

19 POL MALE RECP	
DWG. NO.	REV
11NL1911P_77	Δ

MIN-19MR-ZZ $\overline{}$ SHEET 1 OF 1 WEIGHT:

RATINGS:

PIN 12 PINS 5 & 7