

Swivel-style Universal Brackets (SUB)

Swivel-style Universal Bracket Attach threaded barrel photoelectric and ultrasonic sensors, mini photoelectrics, as well as limit switch-style devices having M30 threaded bases. Achieve easy aiming and secure mounting with these durable, glass-filled nylon brackets.



Features

- Durable Glass-filled Nylon Construction
- Regular or Extended Base Models
- Sizes for 12, 18 and 30mm Threaded Sensors
- Blank for mounting mini photoelectrics
- T-Slot mounting fastener option

Benefits

- Easy Sensor Installation and Setup
- Corrosion-Resistant
- Stock Mounting Solutions
- Direct attachment to T-Slot



SUB-30 with M30 x 1.5 threaded barrel ultrasonic sensor.



SUB-30 with photoelectric having a M30 x 1.5 threaded base.



User-drilled, SUB-MPB shown with mini photoelectric sensor.



SUB-30-TS, supplied with all fasteners for T-Slot mounting.

Model No.	Thread
SUB-12	M12 X 1
SUB-18	M18 X 1
SUB-30	M30 X1.5
SUB-MPB	User drilled & tapped, or use double-backed adhesive tape.
Notes	<p>1) Order by model number. 2) For extended base option, use SUBE in the model number, for example SUBE-30. 3) For included T-Slot fasteners, add "TS" to the end of the model number, for example SUBE-30-TS. 4) T-Slot option fasteners adapt SUB's to most 30mm size and up extruded aluminum profiles. 5) Housing material is glass-filled Nylon and fasteners are stainless steel. 6) User provides sensor fasteners on MPB versions. 7) MPB blank is black Delrin®.</p>

