CABLES

Connection cable, straight
M12/8 pin, straight connector, shielded, for power supply and I/O.

Connection cable 90°
M12/8 pin, 90° connector, shielded, for power supply and I/O.

Ethernet crossover cable
1 m, RJ45 both ends, shielded.

Ethernet cable
M12/8 pin (or 4 pin, D coded), and RJ45 for connection to network or PC.

Interface cable
RS422, M 12/5 pin.

Interface cable
RS422, M 12/5 pin, Sub-D 9 pin.

Lighting cable
2x M12/8 pin straight or 90° (both connectors identical).

Lighting cable
M12/8 pin, bare wire ends for permanent lighting mode.

Item no.	Part name	Description
902-51708	C L8FSK-2m-G-PUR	Connection cable, 2 m, straight connector, shielded
902-51709	C L8FSK-5m-G-PUR	Connection cable, 5 m, straight connector, shielded
902-51710	C L8FSK-10m-G-PUR	Connection cable, 10 m, straight connector, shielded
902-51711	C L8FSK-2m-W-PUR	Connection cable, 2 m, 90° connector, shielded
902-51712	C L8FSK-5m-W-PUR	Connection cable, 5 m, 90° connector, shielded
902-51713	C L8FSK-10m-W-PUR	Connection cable, 10 m, 90° connector, shielded
902-51715	CI L8FSK/RJ45S-3m-GG-PVC	Ethernet cable, 3 m, M12, 8 pin/RJ45, shielded, (not crossed)
902-51736	CI L8FSK/RJ45S-3m-GG-PVC-G	Ethernet cable, 3 m, M12, 8 pin/RJ45, shielded, (crossed)
902-51695	CI RJ45S 1m K	Ethernet crossover cable, 1 m, RJ45, shielded
902-51696	CI L5FK-3m-G-PUR	Interface cable, 3 m, straight connector
902-51697	CI L5FK-xm-G-PUR	Interface cable, x m, straight connector, (max. 25 m)
902-51698	CI L5FK-3m-W-PUR	Interface cable, 3 m, 90° connector
902-51699	CI L5FK-xm-W-PUR	Interface cable, x m, 90° connector (max. 25 m)
902-51757	CI L5FK-D9MS-3m-G-PUR	Interface cable for I/O extension, 3 m, straight connector
902-51758	CI L5FK-D9MS-3m-W-PUR	Interface cable for I/O extension, 3 m, 90° connector
902-51759	CI L5FK-D9MS-5m-G-PUR	Interface cable for I/O extension, 5 m, straight connector
902-51760	CI L5FK-D9MS-5m-W-PUR	Interface cable for I/O extension, 5 m, 90° connector
902-51694	AA-RJ45	Ethernet connector RJ45, shielded
902-51761	CI L4MGK/RJ45G-S-3m-PUR	Ethernet cable, 3 m, M12, straight connector, 4 pin, D coded/RJ45, shielded (not crossed)
902-51762	CI L4MGK/RJ45G-SG-3m-PUR	Ethernet cable, 3 m, M12, straight connector 4 pin, D coded/RJ45, shielded (crossed)
902-51763	CI L4MGK/RJ45G-S-5m-PUR	Ethernet cable, 5 m, M12, straight connector, 4 pin, D coded/RJ45, shielded (not crossed)
902-51764	CI L4MGK/RJ45G-SG-5m-PUR	Ethernet cable, 5 m, M12, straight connector, 4 pin, D coded/RJ45, shielded (crossed)
902-51765	CI L4MGK/RJ45G-S-10m-PUR	Ethernet cable, 10 m, M12, straight connector, 4 pin, D coded/RJ45, shielded (not crossed)
902-51766	CI L4MGK/RJ45G-SG-10m-PUR	Ethernet cable, 10 m, M12, straight connector, 4 pin, D coded/RJ45, shielded (crossed)
902-51767	CI L4MWK/RJ45G-S-3m-PUR	Ethernet cable, 3 m, M12, 90° connector, 4 pin, D coded/RJ45, shielded (not crossed)
902-51768	CI L4MWK/RJ45G-SG-3m-PUR	Ethernet cable, 3 m, M12, 90° connector, 4 pin, D coded/RJ45, shielded (crossed)
902-51769	CI L4MWK/RJ45G-S-5m-PUR	Ethernet cable, 5 m, M12, 90° connector, 4 pin, D coded/RJ45, shielded (not crossed)
902-51770	CI L4MWK/RJ45G-SG-5m-PUR	Ethernet cable, 5 m, M12, 90° connector, 4 pin, D coded/RJ45, shielded (crossed)
902-51771	CI L4MWK/RJ45G-S-10m-PUR	Ethernet cable, 10 m, M12, 90° connector, 4 pin, D coded/RJ45, shielded (not crossed)
902-51772	CI L4MWK/RJ45G-SG-10m-PUR	Ethernet cable, 10 m, M12, 90° connector, 4 pin, D coded/RJ45, shielded (crossed)
902-51773	CI L8MGK/L4MGK-S-0.2m-PVC	Ethernet adapter cable, M12, 8 pin, male, M12, 4 pin, D coded, male, 0.2 m, straight connector, patch, shielded
902-51751	CI L4FGK / L8FGK-S-0.2m-PVC	Ethernet adapter cable M12, 4 pin D coded, female / M12, 8 pin, female, 0.2 m, straight connector, patch, shielded
902-51717	CB L8FSK/L8FSK- 0.5m-GG-PUR	Lighting cable 2 × M12/8 pin, 0.5 m, straight connector, shielded
902-51718	CB L8FSK/L8FSK- 0.5m-WW-PUR	Lighting cable 2 × M12/8 pin, 0.5 m, 90° connector, shielded
902-51719	CB L8FSK/L8FSK- 2m-GG-PUR	Lighting cable 2 × M12/8 pin, 2 m, straight connector, shielded
902-51756	CB L4 MG 10m PUR	Lighting cable 1 × M12/4 pin, 10 m, for the direct connection of all lightings except LF 45 and LFR 45